AUSTRALIAN SAILING (AS) SPECIAL REGULATIONS EQUIPMENT AUDIT FORM



CATEGORY		NOHULLS ULTIHULLS		es close to shorelir s, with effective re	ne in prote scue ava	ected waters, ilability	daylight
DATE OF AUDIT				NAME:			
				stated in Notice of Race.			s required
owner Details	age to main	itain compliance.	Subject to	spot checks Special Regu	ilation (SR) 2	.02.2.	
OWNER(S) NAME(S):							
OWNER(S) CLUB(S):							
BOAT DETAILS							
LH:				BOAT REGISTRATION N	O:		
DISPL (tonnes):				VARIABLE (WATER) BAL	LAST: YE	S NO	
HULL COLOUR:							
DECK COLOUR:				DISTINGUISHING MARK	S:		
MAX CREW:							
DECLARATION BY	PERSON II	N CHARGE					
all of the boat's equipment Signed by Person in C	t as specified i	n the current AS Spe	ecial Regulati	.02.2, 1.02.3 and 2.03.1. I unons, and ensure it will be on bate:	ooard for each	race.	orking order
	MS – This a	audit is not valid	until the o	utstanding items have b	een re-insp		
Outstanding Item				Re-Inspected by		AS No.	Date
	100 DE01 /	DATION					
EQUIPMENT AUDIT I have checked the abover the AS Special Regulations	mentioned boa	at in accordance with	SR 2.02.1, a	s summarised in the following	list, and the ite	ems listed were comp	liant as per
Audited by AS NEA:(print name)				Signed by AS NEA:			
AS Number:				Date:			
EARLIEST EXPIRY	1		not appli	cable 'n/a' if relevant			
ITEM	EARLIEST EXPIRY	UPDATED EARLIEST EXPIRY	AUDITOR	ITEM	EARLIEST EXPIRY	UPDATED EARLIEST EXPIRY	AUDITOR
Fire ext (12 mth.)				Lifejackets			
NOTE: Some club	bs will not ac	cept self-servicing o	of lifejackets	s. Check with the club for sp	ecific require	ments.	



Page 1 of 2 Version 1.5 – 14 May 2024

AUSTRALIAN SAILING (AS) SPECIAL REGULATIONS EQUIPMENT AUDIT FORM



CATEGORY 6

MONOHULLS & Races close to shoreline in protected waters, daylight hours, with effective rescue availability

BOAT NAME:

This section to be completed and ticked or initialled by person in charge (P) and auditor(A). If item not applicable, mark 'n/a' or dash '-'

Reg	Structural Fixed Deck Items		Α	
2.03.1	Equipment functions & adequate for intended use			
2.03.2	Ballast & heavy equipment secured			
3.01 -	Section 3 Part 1 – Structural Features, Stability. See			
3.01 -	Keel and Rudder Inspection Form, and Organising			
3.03	Authority requirements			
3.06.1	(b) Enclosed cabin, ≥ 5.5m LH, and carrying fuel below			
0.00.1	decks, 2 exits			
3.07.1	No hatches forward of maximum beam open inwards			
	except if size < 0.071 m ²			
2.07.2	(a)(i) Hatches above water when heeled 90°			
3.07.2	(a)(iii) Non-conforming hatches; size < 0.071 m ²			
	(a)(iii) Non-conforming hatches kept shut while racing Non-conforming hatches labelled			
3.07.3	'Not to be opened at sea'			
3.08.1	Cockpit strong, self-draining, & watertight (3.08.2)			
3.08.3	If Fitted, bilge pump outlet not connected to cockpit			
If fitted	drain			
	Number of cockpit drains required: <8.5 m: 2 x 25 mm			
3.08.7	Age/Series Date pre 07/77 & >8.5 m; 2 x 25 mm			
	Age/Series Date post 07/77 & >8.5 m; 4 x 20 mm			
3.08.8	Multihull minimum drain sizes after allowance for			
0.00.0	screen 20 cm ² per m ³ of cockpit			
3.20.6	Bilge pump not to discharge into closed cockpit			
3.20.7	Bilge pump not connected to cockpit drains			
If Fitted	Bilge pump minimum suction bore 25 mm			
	Bilge pump & strum boxes accessible Hull Identification, min 50 mm; name & state rego;			
3.28.1	OR name, sail number & club			
4.01.1	Sail numbers as per RRS 77 and Appendix G			
Reg	Structural/Fixed Items Below	Р	Α	
ivea	(a)(i) Lifelines uncoated stainless steel wire, or	_	$\overline{}$	
	(a)(iii) HMPE rope of minimum diameter			
	(a)(iii) I iivii E ropo oi iiiiiiiiiiiaiii alaiiiotoi			
1	(b) Loose sleeve permitted			
3.12.6	(b) Loose sleeve permitted (d) Gap secured by lanyard < 100 mm:Lanyard			
3.12.6 If fitted	(b) Loose sleeve permitted (d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually			
	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually			
	(d) Gap secured by lanyard ≤ 100 mm;Lanyard			
	 (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m – 13 m: 4 mm; LH > 13 m: 5 mm 			
	 (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m – 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway 			
	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff			
If fitted	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking			
If fitted	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign			
If fitted	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light			
If fitted	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams			
If fitted	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment			
If fitted	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams			
3.17 If fitted	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment ventilated overboard Dedicated starter battery if electric starter is only method of starting			
3.17 If fitted 3.24.6 If fitted 3.24.7	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment ventilated overboard Dedicated starter battery if electric starter is only			
3.17 If fitted 3.24.6 If fitted 3.24.7 If fitted	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment ventilated overboard Dedicated starter battery if electric starter is only method of starting Separate generators, if carried, securely covered and permanently installed			
3.17 If fitted 3.24.6 If fitted 3.24.7 If fitted 3.24.8	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment ventilated overboard Dedicated starter battery if electric starter is only method of starting Separate generators, if carried, securely covered and permanently installed Fuel tank shut off valve/cock if fuel can escape or			
3.17 If fitted 3.24.6 If fitted 3.24.7 If fitted	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment ventilated overboard Dedicated starter battery if electric starter is only method of starting Separate generators, if carried, securely covered and permanently installed Fuel tank shut off valve/cock if fuel can escape or siphon			
3.17 If fitted 3.24.6 If fitted 3.24.7 If fitted 3.24.8	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment ventilated overboard Dedicated starter battery if electric starter is only method of starting Separate generators, if carried, securely covered and permanently installed Fuel tank shut off valve/cock if fuel can escape or siphon (a) Petrol tanks – see regulation			
3.17 If fitted 3.24.6 If fitted 3.24.7 If fitted 3.24.8	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment ventilated overboard Dedicated starter battery if electric starter is only method of starting Separate generators, if carried, securely covered and permanently installed Fuel tank shut off valve/cock if fuel can escape or siphon (a) Petrol tanks – see regulation (b) Diesel tanks metal or other certified material			
3.17 If fitted 3.24.6 If fitted 3.24.7 If fitted 3.24.8 If fitted	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment ventilated overboard Dedicated starter battery if electric starter is only method of starting Separate generators, if carried, securely covered and permanently installed Fuel tank shut off valve/cock if fuel can escape or siphon (a) Petrol tanks – see regulation (b) Diesel tanks metal or other certified material (c) Fuel lines comply			
3.17 If fitted 3.24.6 If fitted 3.24.7 If fitted 3.24.8 If fitted 3.24.9	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment ventilated overboard Dedicated starter battery if electric starter is only method of starting Separate generators, if carried, securely covered and permanently installed Fuel tank shut off valve/cock if fuel can escape or siphon (a) Petrol tanks – see regulation (b) Diesel tanks metal or other certified material (c) Fuel lines comply (d) Outboard tanks secured on deck or ventilated			
3.17 If fitted 3.24.6 If fitted 3.24.7 If fitted 3.24.8 If fitted	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment ventilated overboard Dedicated starter battery if electric starter is only method of starting Separate generators, if carried, securely covered and permanently installed Fuel tank shut off valve/cock if fuel can escape or siphon (a) Petrol tanks − see regulation (b) Diesel tanks metal or other certified material (c) Fuel lines comply (d) Outboard tanks secured on deck or ventilated compartment; manufacturer supplied or recognised			
3.17 If fitted 3.24.6 If fitted 3.24.7 If fitted 3.24.8 If fitted 3.24.9	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment ventilated overboard Dedicated starter battery if electric starter is only method of starting Separate generators, if carried, securely covered and permanently installed Fuel tank shut off valve/cock if fuel can escape or siphon (a) Petrol tanks − see regulation (b) Diesel tanks metal or other certified material (c) Fuel lines comply (d) Outboard tanks secured on deck or ventilated compartment; manufacturer supplied or recognised national standard			
3.17 If fitted 3.24.6 If fitted 3.24.7 If fitted 3.24.8 If fitted 3.24.9	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment ventilated overboard Dedicated starter battery if electric starter is only method of starting Separate generators, if carried, securely covered and permanently installed Fuel tank shut off valve/cock if fuel can escape or siphon (a) Petrol tanks − see regulation (b) Diesel tanks metal or other certified material (c) Fuel lines comply (d) Outboard tanks secured on deck or ventilated compartment; manufacturer supplied or recognised national standard (e) Petrol not below decks in portable containers			
3.17 If fitted 3.24.6 If fitted 3.24.7 If fitted 3.24.8 If fitted 3.24.9 If fitted	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment ventilated overboard Dedicated starter battery if electric starter is only method of starting Separate generators, if carried, securely covered and permanently installed Fuel tank shut off valve/cock if fuel can escape or siphon (a) Petrol tanks − see regulation (b) Diesel tanks metal or other certified material (c) Fuel lines comply (d) Outboard tanks secured on deck or ventilated compartment; manufacturer supplied or recognised national standard			
3.17 If fitted 3.24.6 If fitted 3.24.7 If fitted 3.24.8 If fitted 3.24.9	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment ventilated overboard Dedicated starter battery if electric starter is only method of starting Separate generators, if carried, securely covered and permanently installed Fuel tank shut off valve/cock if fuel can escape or siphon (a) Petrol tanks − see regulation (b) Diesel tanks metal or other certified material (c) Fuel lines comply (d) Outboard tanks secured on deck or ventilated compartment; manufacturer supplied or recognised national standard (e) Petrol not below decks in portable containers (f) Flexible fuel tank not permitted			
3.24.6 If fitted 3.24.7 If fitted 3.24.8 If fitted 3.24.9 If fitted	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment ventilated overboard Dedicated starter battery if electric starter is only method of starting Separate generators, if carried, securely covered and permanently installed Fuel tank shut off valve/cock if fuel can escape or siphon (a) Petrol tanks − see regulation (b) Diesel tanks metal or other certified material (c) Fuel lines comply (d) Outboard tanks secured on deck or ventilated compartment; manufacturer supplied or recognised national standard (e) Petrol not below decks in portable containers (f) Flexible fuel tank not permitted (b)(iii) Permanently installed (new installations DSC capable), or waterproof handheld, VHF transceiver	P.		
3.17 If fitted 3.24.6 If fitted 3.24.7 If fitted 3.24.8 If fitted 3.24.9 If fitted	(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Lifeline size minimum: LH < 8.5 m: 3 mm; LH 8.5 m − 13 m: 4 mm; LH > 13 m: 5 mm Cooking stove/heating appliance safe use in seaway e.g. Gimballed with accessible shutoff Gas or methylated spirits only fuels for cooking "REMEMBER Turn Off Gas At Bottle" sign Gas detection for permanent pilot light Disposable gas canisters ≤ 225 grams Gas bottle, spare canisters in separate compartment ventilated overboard Dedicated starter battery if electric starter is only method of starting Separate generators, if carried, securely covered and permanently installed Fuel tank shut off valve/cock if fuel can escape or siphon (a) Petrol tanks − see regulation (b) Diesel tanks metal or other certified material (c) Fuel lines comply (d) Outboard tanks secured on deck or ventilated compartment; manufacturer supplied or recognised national standard (e) Petrol not below decks in portable containers (f) Flexible fuel tank not permitted (b)(iii) Permanently installed (new installations DSC	P		

3.24.10	If no motor & <5.5m LH, oars or paddles x 2; blade	
3.24.10	area 0.04m ²	
4.04.2	If motor or stove fitted: 1 x fire extinguishers 1A:10BE	
If fitted	dry powder min or equiv.	
4.04.4	Fire blanket (for cooking device with open flame)	
	(a) Anchors & ground tackle as per Table 1	
4.05.1	(b) Anchor & warp sizes Table 2 or Table 3	
	Anchor 1 Typekg/size	
4.07.4	First aid kit, waterproof container; contents as listed at	
4.07.9	end of this form (alternative brands permitted)	
4.40.0	Current AS "Racing Rules of Sailing" and "Special	
4.10.3	Regulations Part 1"; electronic or hard copy	
4.15.3	Sharp knife sheathed, restrained in or near cockpit	
4.16.1	Name on all buoyant equipment & items	
4.16.2	Personal lifejacket marked to identify owner	
4.17	Retroreflective tape on lifebuoys, lifeslings, liferafts	
4.26	Retrieval method of crew from water	
	(i) Lifejacket ≥ 50N in service	
5.01.1	Number (1 per crew)	
	(See regulation for compliance standards)	

4.07.9 First Aid Kit Contents List – within expiry date				
NON-PRESCRIPTION	Р	Α		
Soluble Aspirin (e.g.Disprin) x 20				
Disposable gloves x 10				
Crepe bandages 75 mm x 1.5 m x 2				
Low absorbency non-adherent dressing/plain gauze (e.g. Melolin) x 5				
Bandaids or equivalent rollof bandaid x 20				
Normal saline 30 ml x 2				
Sunscreen 30+ 250 ml x 1				
Scissors, stainless steel x 1				
CPR mask or 6 face shields				

END OF FORM

As this form is for national use and portability, please use a separate checklist page for additional club/race organiser requirements



Page 2 of 2 Version 1.5 – 14 May 2024